

FEATURES

Hato Bronze aerosol acrylic lacquer is made from special quality pearl pigments, giving bronze shining reminiscent as a natural looks. With our advanced manufacturing techniques, the shade of Hato bronze paint is miraculously gorgeous with high weather durability and can use both interior and exterior without color deteriorating over 10 years.

TECHNICAL INFORMATION

Type	Aerosol Acrylic Lacquer Bronze Paint (Spray)
Color	Bronze
Film appearance	Gloss
Pack size	400 cc
Flash point	-40
Wet film thickness	100-125 Microns
Dry film thickness	10.50-13.15 Microns
Theoretical coverage	25-31 Sq.m./coat/400 cc
Touch dry (25-30°C)	10 Minutes
Recoat dry (25-30°C)	10 Minutes
Full cure (25-30°C)	1 Hour

APPLICATION

1. Shake can thoroughly 2 minutes before using and shakes periodically during spray
 2. Spray from a distance of about 6-8 inches with opening in spray head pointed towards object. Press level down with index finger, keeping can in motion from side to side so that coating is deposited evenly.
 3. Spray several thin coatings with an interval of 10 minutes
 4. After spraying turn can upside down and press spray head to clean the spray nozzle
- It is advisable to finish the whole can once start to use, to avoid the block of dry paint in the valve after use.

APPLICATION SYSTEM

Surface Preparation

Surface must be clean, dry and free from oil, grease and contaminants before painting. For previously painted surfaces, remove all unstable paint film, loose chalk, dust and foreign matter. Substrate sanding is preferable especially on smooth surface.

Coating system

Primer

Apply 1 coat of HATO Acrylic Primer

Topcoat

Apply 2 coats of HATO Aerosol Acrylic Lacquer Bronze Paint.

HANDLING AND STORAGE

Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.

HEALTH AND SAFETY

Use under well ventilated conditions. Avoid skin contact.