

FEATURES	Hato Acrylic Primer for Gold Paint is made of 100% pure acrylic resin with premium pigment suitable for exterior & interior application. The special quality pigment that delivers rich & beautiful long lasting colours. Excellent adhesion, durable and can resist to harsh weathering conditions. Anti-fungus and algae. No lead and mercury added.
TECHNICAL INFORMATION	
Type	Acrylic Primer for Gold Paint (Water-base)
Color	Yellow
Film appearance	Semi-Gloss
Pack size	1 US Gallon, ¼ US Gallon
Flash point	-
Wet film thickness	110-125 Microns
Dry film thickness	41.00-46.30 Microns
Theoretical coverage	30-35 Sq.m./coat/Gallon
Touch dry (25-30°C)	20-30 Minutes
Recoat dry (25-30°C)	1 Hour
Full cure (25-30°C)	2 Hours
APPLICATION	
Tools	Brush, Roller or Spray gun
Diluent	TG-09 or Clean water
Dilution (%)	10-20%
APPLICATION SYSTEM	
Surface Preparation	
New Surface	Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any loose material and cement splashes.
Old Surface	Polish the surface with sandpaper to enhance better adhesion. Chalky or peeling surface must be thoroughly cleaned with water and leave completely dried. Apply 1-2 coats of Hato Contact primer.
Coating system	
Primer	Apply 1-2 coats of Hato Acrylic Primer for Gold paint (AG-33 Yellow)
Topcoat	Apply at least 2-3 coats (Brush) of Hato Gold
HANDLING AND STORAGE	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
HEALTH AND SAFETY	Use under well ventilated conditions. Avoid skin contact.