

<p><b>FEATURES</b></p>	<p>Hato Body Schutz works as a protective coating with sound deadening qualities designed for cars, trucks and vans. Our black, rubberized coating bonds to a wide variety of surfaces helps protect vehicles from corrosion and reduce road noise. Its high build capabilities add a layer of protection to shield the underside of a vehicle from moisture, road salt and stones. This layer of protection helps guard against corrosion, rust and chipping. The rubberized coating helps reduce road noise helping create a quieter and more pleasant ride inside the vehicle for passengers. It is easy to apply and provides good coverage with a consistent final appearance. High-build capabilities allow you to customize the layer to your desired thickness.</p>
<p><b>TECHNICAL INFORMATION</b></p> <p>Type</p> <p>Color</p> <p>Film appearance</p> <p>Pack size</p> <p>Solid by volume</p> <p>Solid by weight</p> <p>Specific gravity</p> <p>Flash point</p> <p>Wet film thickness</p> <p>Dry film thickness</p> <p>Theoretical coverage</p> <p>Touch dry (25-30°C)</p> <p>Recoat dry (25-30°C)</p> <p>Full cure (25-30°C)</p>	<p>Bituminous</p> <p>Gray and Green</p> <p>Semi-gloss</p> <p>1 Gallon</p> <p>47 ± 2%</p> <p>54 ± 2%</p> <p>0.88-0.94</p> <p>35 °C</p> <p>75-100 Microns</p> <p>35-50 Microns</p> <p>40-45 Sq.m./coat/gallon</p> <p>Remark - Actual Surface coverage will depend on surface irregularities, Mixing, Application Condition method and technique; as well as the structure and dimensions of the object to be coated</p> <p>10-30 Minutes</p> <p>2-4 Hours at 25°C</p> <p>7 Days</p>
<p><b>APPLICATION</b></p> <p>Tools</p> <p>Diluent</p> <p>Dilution (%)</p>	<p>Brush or Spray gun</p> <p>Turpentine or white spirit</p> <p>Brush 10-20% / Spray gun 100-150 %</p>
<p><b>APPLICATION SYSTEM</b></p> <p>Surface Preparation</p> <p>Coating system</p>	<p>The substrate must be free from rust, mill scale, loose particles, and waxy contaminate</p> <p>The product can be applied over bare metal or primer.</p> <p>Clean and dry surface with soap and water</p> <p>Apply in relatively light coats, allowing for the solvent to evaporate somewhat between coats. Build to desired thickness</p>
<p><b>HANDLING AND STORAGE</b></p>	<p>Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.</p>
<p><b>HEALTH AND SAFETY</b></p>	<p>Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Avoid skin contact, do not breathe or inhale mist. For details information on the health and safety hazards and precautions for use of this product, please refer to the Safety datasheet</p>