

| | |
|------------------------------|---|
| FEATURES | <p>Hato Acrylic Primer for Gold Paint is made of 100% pure acrylic resin with premium pigment suitable for exterior & interior application. The special quality pigment that delivers rich & beautiful long lasting colours. Excellent adhesion, durable and can resist to harsh weathering conditions. Anti-fungus and algae. No lead and mercury added.</p> |
| TECHNICAL INFORMATION | |
| Type | Acrylic Primer for Gold Paint (Solvent-base) |
| Color | White |
| Film appearance | Semi-Gloss |
| Pack size | 1 US Gallon, ¼ US Gallon |
| Flash point | 6 |
| Wet film thickness | 110-125 Microns |
| Dry film thickness | 43.98-49.98 Microns |
| Theoretical coverage | 30-35 Sq.m./coat/Gallon |
| Touch dry (25-30°C) | 3-5 Minutes |
| Recoat dry (25-30°C) | 1 Hour |
| Full cure (25-30°C) | 4 Hour |
| APPLICATION | |
| Tools | Brush, Roller or Spray gun |
| Diluent | TG-04 or Thinner acrylic |
| Dilution (%) | Brush: 10-20%, Spray gun: 150% |
| APPLICATION SYSTEM | |
| Surface Preparation | <p>Surface must be clean, dry and free from oil, grease and contaminants before painting. For previously painted surfaces, remove all unstable paint film, loose chalk, dust and foreign matter. Substrate sanding is preferable especially on smooth surface.</p> |
| Coating system | |
| Primer | Apply 1-2 coat of HATO Acrylic Primer No. G-116 (White) |
| Topcoat | Apply 2-3 coats of HATO Gold Paint. |
| HANDLING AND STORAGE | <p>Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.</p> |
| HEALTH AND SAFETY | <p>Use under well ventilated conditions. Avoid skin contact.</p> |