

<b>FEATURES</b>	NOC is emulsion Paint formulated with fungus and mould resistance with no lead and mercury added. It is ideal for the protection and decoration for interior and exterior masonry substrates such as plaster, concrete, brick, gypsum board. Good adhesion. Good algae resistance, no lead and mercury added.
<b>TECHNICAL INFORMATION</b>	
Type	100% Pure Acrylic Emulsion
Color	Copper red
Film appearance	Matt
Pack size	1 Gallons
Solid by volumn	35.42-36.48
Solid by weight	53.54-55.15
Specific gravity	1.379-1.420
Wet film thickness	95-110 micron
Dry film thickness	33.65-38.96 micron
Theoretical coverage	35-40 Sq.m./coat/gallon
Touch dry (25-30°c)	30 Minutes
Recoat dry (25-30°c)	2 Hours
Full cure (25-30°c)	At least 7 Days
<b>APPLICATION</b>	
Tools	Roller, Brush and Spray
Diluent	Clean Water
Dilution (%)	5-10% (roller and brush) / 10-20% (spray)
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	
New Surface	Allow adequate time for surface to dry out completely. Surface must be free from efflorescence. Brush down or scrape off any lose material and cement splashes.
Old Surface	Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days.
<b>Coating system</b>	
Primer	New concrete Surface: Apply 1-2 coats of NOC Super Primer Two in one NO2012 (Water-based) Old Surface: Apply 1-2 coats of NOC Super Primer Two in one NO2012 (Water-based)
Topcoat	Apply at least 2 coats of NOC Emulsion Paint for brick
<b>TIS</b>	-
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.