

Technical Data Sheet

Hato Lacquer G-031 Hato Acrylic lacquer for Gold Paint

FEATURES	Hato Acrylic lacquer G-031 (Spray) for Gold Paint is a high quality lacquer coating that provides a smooth,
	durable, ultra-hard, gloss finish on substrate. Can resist to harsh weathering conditions. No lead and
TEOLINICAL INFORMATION	mercury added.
TECHNICAL INFORMATION	
Туре	Lacquer
Color	Clear
Film appearance	Gloss
Pack size	400 cc
Flash point	-40
Wet film thickness	100-125 Microns
Dry film thickness	12.86-16.08 Microns
Theoretical coverage	25-31 Sq.m./coat/400 cc
Touch dry (25-30°c)	10 Minutes
Recoat dry (25-30°c)	10 Minutes
Full cure (25-30°c)	1 Hour
APPLICATION	Shake can thoroughly 2 minutes before using and shakes periodically during spray
	2. Spray from a distance of about 6-8 inches with opening in spray head pointed towards object.
	Press level down with index finger, keeping can in motion from side to side so that coating is
	deposited evenly.
	Spray several thin coatings with an interval of 10 minutes
	4. After spraying turn can upside down and press spray head to clean the spray nozzle
	It is advisable to finish the whole can once start to use, to avoid the block of dry paint in the valve
	after use.
APPLICATION SYSTEM	
Surface Preparation	
	Surface must be clean, dry and free from oil, grease and contaminants before painting.
Coating system	Apply at least 1-2 coats of Hato Lacquer G-031
HANDLING AND STORAGE	The product must be stored in accordance with national regulations. Storage conditions are to keep the
	containers in a dry, cool, well ventilated space and away from source of heat and ignition. Containers must
	be kept tightly closed.
HEALTH AND SAFETY	Please observe the precautionary notices displayed on the container. Use under well ventilated conditions.
	Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be remove with
	suitable cleanser, soap and water. Eyes should be well flushed with clean water and medical attention
	sought immediately.