

<b>FEATURES</b>	Hato Heavy Bodied Paint Remover is an extremely strong stripper that effectively removes paint, varnish, lacquer, shellac, epoxy, urethane, latex or any synthetic coating. The remover liquid would infiltrate through the paint layers until they are skinned off without damage the material of the base surface. It can be used on wood, metal, concrete and masonry.
<b>TECHNICAL INFORMATION</b>	
Type	Mixed Organic Solvents
Color	Clear
Film appearance	-
Pack size	1, 1/4 Gallon
Solid by volumn	-
Solid by weight	2.10 %
Flash point	201 C°
Specific gravity	1.13-1.21
Wet film thickness	Non film
Dry film thickness	Non film
Theoretical coverage	15-20 minutes
Touch dry (25-30°c)	-
Recoat dry (25-30°c)	-
Full cure (25-30°c)	-
<b>APPLICATION</b>	
Tools	Brush
Dilution (%)	Ready to use without any dilution needed.
<b>APPLICATION SYSTEM</b>	
<b>Surface Preparation</b>	The surface must be completely dry and free from dust and grease. Always wear protective gloves and work in an airy area.
<b>Coating system</b>	<p>Wear chemical-resistant gloves and chemical splash goggles.</p> <p>Pour into a metal container and apply with a paintbrush to a small area. Brush in one direction only.</p> <p>Leave the area and let the stripper do the work. After 15 minutes, tests scrape a small area to see if finish is ready for removal. Remove loosened finish by gently scraping in direction of wood grain with a plastic stripping tool. A toothbrush, toothpick or stripping brush will help remove old finish buried in recesses.</p> <p>Multiple coats or stubborn finishes may require repeat application.</p> <p>Use a clean abrasive pad dipped in After Wash or Odorless Mineral Spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before refinishing.</p>
<b>HANDLING AND STORAGE</b>	Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed.
<b>HEALTH AND SAFETY</b>	Use under well ventilated conditions. Avoid skin contact.