

| | |
|------------------------------|---|
| FEATURES | NOC CONTACT PRIMER water-based is made from special quality acrylic resin suitable for old concrete especially for chalking and loose or scaling paint. Delivers strong adhesion, stain blocking, stain resistance, anti-fungus & algae and low odor. Environmentally friendly with no-added lead and mercury. |
| TECHNICAL INFORMATION | |
| Type | Acrylic resin (Water-based) |
| Color | Clear |
| Film appearance | Matt |
| Pack size | 1, 2.5 and 5 US Gallons |
| Solid by volumn | 14.422 – 14.855 |
| Solid by weight | 15.50 – 15.97 |
| Specific gravity | 1.014-1.044 |
| Wet film thickness | 95-110 microns |
| Dry film thickness | 13.70-15.86 microns |
| Theoretical coverage | 35-40 Sq.m./coat/gallon |
| Touch dry (25-30°c) | 30 Minutes |
| Recoat dry (25-30°c) | 2 Hours |
| Full cure (25-30°c) | 1 Day |
| APPLICATION | |
| Tools | Roller, Brush and Spray |
| Diluent | Ready to use. No need to mix with clean water |
| Dilution (%) | - |
| APPLICATION SYSTEM | |
| Surface Preparation | |
| Old Surface | If previously paintwork is still in good condition washing down with clean water or brushing to remove dust and dirt. Powdery and chalky surfaces must be scrubbed and cleaned with water. Fungus and Mildew growth must be clean off with hypochlorite solution and allow for drying out at least 2-3 days. |
| Coating system | |
| Primer | Apply 1-2 coat of NOC Contact Primer (NO2011) |
| Topcoat | Apply at least 2 coats of NOC Acrylic Emulsion Paint |
| TIS | - |
| HANDLING AND STORAGE | Keep the containers in a dry, cool, well ventilated space and away from heat. Containers must be kept tightly closed. |
| HEALTH AND SAFETY | Use under well ventilated conditions. Avoid skin contact. |